

## DVR-F1216-4M

4MP 16CH/2 SATA HYBRID DVR




## KEY FEATURES

- 2 SATA (Each maximum support 6TB)
- Support AHD/TVI/CVI/1080P/4MP
- Support VGA, CVBS, HDMI 1080P HD Output
- Video Compression H.264 High Profile
- 6Ch Audio Input/1 Ch Audio Output
- 4Ch Alarm Input/1 Ch Alarm Output

# DVR-F1216-4M

## 4MP 16CH/2 SATA HYBRID DVR

### DIMENSION



### INTERFACE



### SPECIFICATION

#### VIDEO

Video Compression	H.264 High Profile
Encode Ability	16ch*4MP@8fps/3MP@10fps(AHD), 16ch*1080P@15fps(5 IN 1)
Decode Ability	16ch*4MP@8fps/3MP@10fps(AHD), 16ch*1080P@15fps(5 IN 1)
Preview Ability	16ch*4MP@15fps(AHD) / 16ch*3MP@18fps(AHD) / 16ch*1080P(5 IN 1)
Video Input	Pure Analog: 16ch*4MP@8fps/3MP@10fps(AHD) / 16ch*1080P@15fps/720p(5 IN 1); Mixed Input:16ch*4MP(Analog + IP), Pure Network:16ch*1080P/960P/3MP/4MP;

#### AUDIO

Audio Compression	G711A
Two Way Audio	Support

#### RECORD AND PLAYBACK

Hard Drive	2 SATA(Each maximum support 6T )
Record	Manual/Event/Timer
Playback	16ch(pure local input mode)

#### STORAGE AND BACKUP

Space Occupation	960H:12~20G/ day*channel
	720P:10~20G/ day*channel
	1080P 20~30G/ day*channel
	Audio:691.2M/ day*channel
Backup Mode	USB HDD

#### INTERFACE

Video Input	16ch BNC (AHD/TVI/CVI/CVBS)
Video Output	1ch VGA,1ch HDMI,1ch CVBS
Audio Input	6ch RCA
Audio Output	1ch RCA
Alarm Input	4ch
Alarm Output	1ch
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB

#### GENERAL

Power	12V/4A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	350mm(L)x 295mm(W)x 45mm(H)