D-Link®

5G CPE Router



Experience 5G connection speeds up to 4.6 Gbps (theoretical value) and high-speed Wi-Fi up to 1.8 Gbps (theoretical value) on all your connected devices throughout your home.

DWR-2000M

- Next generation 5G connectivity speeds up to 4.6 Gbps (theoretical value)
- Built-in Wi-Fi AX1800 distributes high-speed, high-performance Wi-Fi to all your connected devices
- Dual-band Wi-Fi with MU-MIMO technology makes 4K streaming, VR gaming or video chatting a breeze
- 1 Gigabit Ethernet LAN port and 1 Gigabit Ethernet WAN/LAN port
- Connect up to 64 devices to your home Wi-Fi
- Latest Wi-Fi security with 128-bit encryption









High-speed 5G Internet

Connect with next-generation 5G speeds up to 4.6 Gbps (theoretical value) and experience lightning-fast downloads, lower latency and reduced congestion



Up to 64 Devices

Connect all of your home's Wi-Fi devices to share a single broadband connection



Dual-Band AX1800

1201 Mbps (5 GHz) + 574 Mbps (2.4 GHz) - Plenty of bandwidth for video streaming, cloud storage, social media, and downloading



SIM Slot

Simply insert you SIM card to share your mobile broadband connection throughout the home



Gigabit Ethernet Ports

High-speed connections for wired devices and wired broadband



Supports IPv6

Future-proof and compatible with the next generation of Internet standards

Hardware Parameters	
Device Interfaces	1 x 10/100/1000 Gigabit Ethernet LAN Port, 1 x 10/100/1000 Mbps Gigabit Ethernet WAN/LAN port, 1 x USB Type C Port, 1 x LTE SIM/USIM Slot, 1 x Reset Hole, 1 x WPS Button, 1 x Power Port, 1 x RJ11 Phone jack
LED	Power, WLAN, 4G LTE, 5G
Antenna Type	2 x 3dBi Internal 2.4G & 5G Dual Band Antenna, Internal 4G/5G Antennas
Wi-Fi Data Rate (theoretical value)	2T2R 2.4GHz 802.11b/g/n / ax, 574 Mbps 2T2R 5.8GHz 802.11a/n/ac/ax, 1201Mbps
Wireless IEEE Standard	802.11a/b/g/n/ac/ax
WAN Interface	DHCP
	Static IP
	PPPoE (PPPoE Pass-through)
Functionality	
Security Protocol	WEP (128bits), 802.11i 128-bit TKIP/AES
Firewall	DoS , IP/MAC Address Filtering
Software	
Device Management	Web UI
Physical	
Hardware version	A3
Size	(L*W*H) 107*107*185mm
Weight	690g
Power Input	12 V 2 A
Operating Temperature	-10 to 40 °C
Storage Temperature	-40 to 70 °C
Operating Humidity	10% to 90% non-condensing
Certifications	CE , RoHS
Band Frequency	
5GNR Sub6 GHz	N1/3/5/7/8/20/28/38/n40/41/77/78
LTE Cat20 FDD	LTE FDD: B1/B3/B5/B7/B8/B20/B28/B32
LTE Cat20 TDD	LTE TDD:B38/B40/B41/B42/B43
WCDMA	B1, B5, B8
Order Information	
DWR-2000M	5G AX1800 CPE Router

